

HFW-DHR-01

Wireless Magnetic Door Holder

Features:

- ▶ Approved to BS EN 1155
- ▶ Easy and Fast installation
- ▶ Local door release button
- ▶ 5 year battery life
- ▶ Utilises standard low cost lithium battery technology
- ▶ Bi-directional wireless communications
- ▶ A Fail Safe monitoring to BS 7273 4:2015 category A, B and C
- ▶ High holding force
- ▶ A Door closed monitoring option



Description

The HFW-DHR-01 wireless magnetic door holder is compatible with all of the FIREwave Wireless Translator and Expander Modules enabling it to be easily integrated into a new or existing wireless system, linked to any wired system or even used as a standalone system. Its fully wireless and battery powered capability means it requires no wiring or power supply, making installation quick, easy and cost effective. The FIREwave range of wireless devices are third party approved and utilise the latest cutting edge technologies and features. The well proven adaptive radio signal processing algorithms combined with the latest in magnet technology ensure the highest levels of life safety and system reliability.

Specification	
Operating frequency range	868 - 870 MHz
Max. radiated power	14dBm (25mW)
Operating frequency channels	7
Communications range	<200m (in open space)
Dimensions	90mm x 135mm x 54mm
Batteries	2 x CR123
Weight	740g
Temp Range (no icing)	-10°C to +55°C
Max Humidity	95%RH
Typical battery life	>5 years
IP rating	30
Holding Force	200N









