

# AJAX

## HUB PLUS



Second-generation intelligent control panel with four communication channels, a new powerful processor, tripled RAM capacity and doubled flash memory capacity. The Hub Plus monitors the operation of all Ajax detectors and instantly alerts the owner and the security company.



The Hub Plus has a Wi-Fi module now, so it is not necessary to lay a cable for connection to the router. The control panel is ready to operate straight out the box. It is set using the mobile application, and the detectors are connected with just one click. The device can be mounted in just a few minutes using the SmartBracket mount.

## Specification

Complete set	Intelligent central unit of the security system with Wi-Fi and Ethernet modules, and dual SIM
Maximum number of connected devices to the hub	150
Video surveillance	Up to 50 cameras or DVRs
Maximum number of users	99
Maximum number of rooms	50
Maximum number of groups	25
Mobile applications	iOS 9.1 and later Android 4.1 and later
Communication channels	Ethernet Wi-Fi 2.4 GHz (802.11 b/g/n) 2G (850/900/1800/1900 MHz) 3G (WCDMA 900/2100 (B8/B1))
Alarm signal	Delivery time: 0.15 s Types of notifications: SMS, call, push
Switching between 2G and 3G	Instant
Switching between SIM cards	4 minutes
Communication with the CMS	Contact ID, SIA
Processor	ARM
Operating system	OS Malevich
Power supply	Mains supply: 110–240 V Battery backup: Li-Ion 2 A · h Up to 16 hours of battery life when Ethernet and Wi-Fi connections are disabled
Operating temperature range	–10°C to +40°C
Remote set up	+
Dimensions	163 x 163 x 36 mm
Weight	350 g
Complete set	Ajax Hub Plus intelligent central unit SmartBracket mounting panel Power cable Ethernet cable Installation kit User's guide