

AJAX

Hub 2 manages all the Ajax devices in the system to alert users about open doors, broken windows, threats of fire and flooding. If burglars break into your house, Hub 2 transmits pictures from the MotionCam detectors and notifies the alarm response company about the danger. You won't need to live under the constant supervision of the security cameras to know what's going on.



Sends a photo-series when triggered

Delivers packages without Wi-Fi and cables

The motion detectors react to dangerous situations as well as simple oversights. A nanny may bring the children home from the school and forget to disarm the security system, which will raise an alarm. With Hub 2, you won't have to worry in those cases and waste money on the false alarm fines. Open an alarm notification sent by the MotionCam detector to see what happened.

Specification

| Complete set | The radio channel central unit with the support of visual alarm |
|-----------------------------|---|
| | verification detectors |
| nstallation | Indoors |
| Connected devices | 100 |
| Video surveillance support | Up to 25 cameras or DVRs |
| Users | 50 |
| Rooms | 50 |
| Security groups | 9 |
| MotionCam detector support | + |
| Communication channels | Ethernet |
| | Two 2G SIM-cards |
| Alarm signals | Delivery time: 0.15 sec |
| | Notification types: SMS, call, push-notification |
| Switching between the | |
| SIM-cards | 4 minutes |
| CMS connectivity | Contact ID, SIA |
| The speed of alarm delivery | |
| to CMS | Instant |
| Software | OS Malevich |
| Power supply | Main supply: 110-240 V |
| | Battery backup: Li-lon 2 A.h |
| | Up to 16 hours of offline operation when the Ethernet is |
| | switched off |
| Jeweller radio technology | Communication range with detectors - up to 2,000 in an open space |
| | Two-way communication between devices |
| | Operating frequencies - 868,0-868,6 Mhz |
| | Self-adjusting RF output power - up to 25 mW |
| | Black encryption based on AES algorithm |
| | Detector polling period - 12-300s |
| | Frequency hopping |
| Wings radio technology | Transmission of visual confirmations |
| | Delivery verification of packages |
| Operating temp range | From -10°C to +40°C |
| Size | 163 x 163 x 36mm |
| Weight | 362g |
| Complete set | Ajax Hub 2 intelligent control panel |
| | SmartBracket mounting panel |
| | Power cable, Ethernet cable, Installation kit, users guide |
| Connected ReX | 5 |
| Scenarios | 32 |
| | |