

AJAX

HUB



The Hub intelligent control panel is a key element of the Ajax security system. The device monitors operation of all Ajax detectors and immediately sends an alarm signal to the owner and the Central Monitoring Station.



Ready to operate straight out the box. It is set using the mobile application, and the detectors are connected with just one click. It can be mounted in just a few minutes using the SmartBracket mount.

Specification

Complete set	The radio channel central unit with GSM & ethernet modules
Maximum number of connected devices to the hub	100
Maximum number of cameras connected to the hub	10
Maximum number of users	50
Maximum number of rooms	50
Maximum number of groups	9
Mobile applications	iOS 9.1 and later Android 4.1 and later
Communication channels	Ethernet, GSM (850/900/1800/1900 MHz)
Alarm signal	Delivery time: 0.15 s Types of notifications: SMS message call, push
Communication with central monitoring	Contact ID, SIA
Processor	ARM
Operating system	OS Malevich
Power supply	Mains supply: 110–240 V Battery backup: Li-Ion 2 A · h Up to 15 hours of offline operation when ethernet is switched off
SIM card support	Micro SIM 2G
Operating temperature range	+5°C to +40°C
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Video surveillance	Up to 10 cameras to DVR
Remote set up	+
Dimensions	163 x 163 x 36 mm
Weight	350 g
Complete set	Ajax Hub intelligent central unit SmartBracket mounting panel Power cable Ethernet cable Installation kit SIM cards (depending on region) User's guide