



HUB KIT 3 KP - WHITE

Kit contains -

1 x HUB

See page 2 for spec



2 x MOTIONPROTECT

See page 3 for spec




1 x KEYPAD

See page 4 for spec



1 x DOORPROTECT

See page 5 for spec



1 x STREETSIREN

See page 6 for spec



1 x HOMESIREN

See page 7 for spec



Hub Specification

Complete set	The radio channel central unit with GSM & ethernet modules
Maximum number of connected devices to the hub	100
Maximum number of cameras connected to the hub	10
Maximum number of users	50
Maximum number of rooms	50
Maximum number of groups	9
Mobile applications	iOS 9.1 and later Android 4.1 and later
Communication channels	Ethernet, GSM (850/900/1800/1900 MHz)
Alarm signal	Delivery time: 0.15 s Types of notifications: SMS message call, push
Communication with central monitoring	Contact ID, SIA
Processor	ARM
Operating system	OS Malevich
Power supply	Mains supply: 110–240 V Battery backup: Li-Ion 2 A · h Up to 15 hours of offline operation when ethernet is switched off
SIM card support	Micro SIM 2G
Operating temperature range	+5°C to +40°C
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Video surveillance	Up to 10 cameras to DVR
Remote set up	+
Dimensions	163 x 163 x 36 mm
Weight	350 g
Complete set	Ajax Hub intelligent central unit SmartBracket mounting panel Power cable Ethernet cable Installation kit SIM cards (depending on region) User's guide

Motion Protect Specification

Classification	Electro-optical combined radio channel security detector
Type of detector	Wireless
Installation method	Indoors
Compatibility	Operates with Hub, Hub Plus, ReX, ocBridge Plus, uartBridge
Sensing element	PIR sensor
Alarm signal delivery time	0.15 s
Motion detection distance	Up to 12 m
Detection angles	Horizontal — 88.5°, Vertical — 80°
Sensitivity	Adjustable, 3 levels
Recommended installation height	2.4 m
Pet immunity	Weight — up to 20 kg, Height — up to 50 cm
Power supply	Battery: CR123A battery, Power supply voltage: 3 V Battery life — up to 7 years
Jeweller radio technology	Communication range with central unit — up to 1,700 m in an open space Two-way communication between devices Operating frequencies — 868.0—868.6 MHz Self-adjusting RF output power — up to 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	Available
Operating temp range	From +5°C to +40°C
Permissible humidity	Up to 75%
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	110x65x50 mm
Weight	86 g
Certification	Grade 2, CE
Complete set	MotionProtect motion detector SmartBracket mounting panel CR123A battery (pre-installed) Installation set User's guide

Keypad Specification

Classification	Radio channel touch keypad
Type of siren	Wireless, touch
Installation method	Indoors
Compatibility	Operates only with Hub, Hub Plus and ReX
Number of buttons	15
Duress code	Yes
Protection against password attack	Yes
Protection against passcode guessing	Yes
Arming/disarming indication	Yes
Power supply	Battery: AAA batteries Power supply voltage: 3 V Battery life — up to 2 years
Jeweller radio technology	Communication range with central unit — up to 1,700 m in an open space Two-way communication between devices Operating frequencies — 868.0-868.6 MHz Self-adjusting RF output power — up to 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	Available
Operating temp range	From -10°C to +40°C
Permissible humidity	Up to 75%
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	150x103x14mm
Weight	197 g
Certification	Grade 2, CE
Complete set	KeyPad touch keyboard SmartBracket mounting panel 4 AAA batteries (pre-installed) Installation set User's guide

Door Protect Specification

Classification	Point magnetic and contact radio channel security detector
Type of detector	Wireless
Installation method	Indoors
Compatibility	Operates with Hub, Hub Plus, ReX, ocBridge Plus, uartBridge
Sensing element	Reed switch
Alarm signal delivery time	0.15 s
Activation threshold	Small magnet — 1 cm, Big magnet — 2 cm
Power supply	Battery: CR123A battery, Power supply voltage: 3 V Battery life — up to 7 years
Jeweller radio technology	Communication range with central unit — up to 1,200 m in an open space Two-way communication between devices Operating frequencies — 868.0—868.6 MHz Self-adjusting RF output power — up to 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	Available
Operating temp range	From +5° C to +40° C
Permissible humidity	Up to 75%
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	Diameter: 20 mm Height: 90 mm
Weight	29g
Certification	Grade 2, CE
Complete set	DoorProtect opening detector SmartBracket mounting panel Two magnets CR123A battery (pre-installed) External contact Installation set User's guide

Street Siren Specification

Classification	Light and sound radio channel security sounder
Type of siren	Wireless
Installation method	Indoors /Outdoors
Compatibility	Operates only with Hub, Hub Plus and ReX
Type of notification	Sound/light
Sound volume level	Adjustable, 81-113 dB at a distance of 1 m
Alarm length	Adjustable, 3-180 s
Indication of armed/ disarmed status	Yes
Alarm signal delivery time	0,15 s
Power supply	Battery: Four CR123A batteries Power supply voltage: 3 V Battery life — up to 5 years Mains supply: DC 12 V±20%
Jeweller radio technology	Communication range with central unit — up to 1,500 m in an open space Two-way communication between devices Operating frequencies — 868.0-868.6 MHz Self-adjusting RF output power — up to 25 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	Available
Operating temp range	From -25° C to +50° C
Permissible humidity	Up to 95%
Protection class of body	IP54
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	200x200x51mm
Weight	528 g
Certification	Grade 2, CE
Complete set	StreetSiren siren SmartBracket mounting panel 4 batteries CR123A (pre-installed) Installation set User's guide

Home Siren Specification

Classification	Radio channel security sounder
Type of siren	Wireless
Installation method	Indoors
Type of notification	Sound
Connector for external LED	Available
Sound volume level	Adjustable, 81-105 dB at a distance of 1 m
Alarm length	Adjustable, 3-180 s
Indication of armed/ disarmed status	Yes
Alarm signal delivery time	0,15 s
Power supply	Battery: Two CR2 batteries Battery: Two CR123A batteries Power supply voltage: 3 V Battery life — up to 5 years
Jeweller radio technology	Communication range with central unit — up to 2,000 m in an open space Two-way communication between devices Operating frequencies — 868.0-868.6 MHz Self-adjusting RF output power — up to 20 mW Block encryption based on AES algorithm Device polling period — 12-300 s
Temperature sensor	Available
Operating temp range	From -10°C to +40°C
Permissible humidity	Up to 75%
Protection class of body	IP50
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	75x76x27mm
Weight	97 g
Certification	Grade 2, CE
Complete set	HomeSiren siren SmartBracket mounting panel Connector for LED indicator Two CR123A batteries (pre-installed) Installation set User's guide