

DATASHEET

| | | |
|-------------------------------|--|--|
| COMPACT-KIT | 20 zone wireless panel, Grade 2, supplied with: control panel, three pet tolerant PIRs, one slim-line door contact, one 2 way fob and a blue sounder (no cover), Eaton Secureconnect enabled | |
| General specifications | Product Name | Eaton i-on Compact intruder system kit |
| | Catalog Number | COMPACT-KIT |
| | EAN | 5060096854494 |
| | Product Length/Depth | 375 mm |
| | Product Height | 190 mm |
| | Product Width | 335 mm |
| | Product Weight | 2.669 kg |
| | Compliances | CE marking |
| | Certifications | |
| Product specifications | Occurrence memory | Yes |
| | On Board Outputs (Panel) | 0 |
| | Out of the box radio zones | 20 |
| | Web browser interface | |
| | On Board Outputs (Plug By) | |
| | VdS Class | None |
| | Users | |
| | With power adaptor | No |
| | Wired internal sounders | |
| | Supports ARD | |
| | Back-up battery size - max | Custom |
| | Radio connection | |
| | Communications options | On Board Ethernet. Plug on GSM, PSTN |
| | Log events | 300 |
| | Number of outputs for optical signal generators | |
| | Number of keypads | |
| | Number of bus devices | |
| | Integrated dial device | |
| | Number of sabotage groups | 21 |
| | Emergency power supply integrated | |
| | EN 50131 Security Grade | 2 |
| | Connection | Radio |
| | Out of the box wired zones | |
| | Cloud support | |
| | Wired external sounders | |

| | | |
|--|-----------------------------|-------|
| | Total capacity zones | |
| | Number of indicator groups | |
| | Operating voltage | 230 V |
| | Custom outputs | |
| | Power supply size | 500mA |
| | Back-up battery quantity | 1 |
| | Radio internal sounders | |
| | Shunt groups | |
| | Suitable for bus connection | |
| | Radio external sounders | |