

DATASHEET

SD-GSM	Eaton speech dialler, GSM, Voice, SMS	
General specifications	Product Name	Eaton speech dialler
	Catalog Number	SD-GSM
	EAN	5060096852605
	Product Length/Depth	25 mm
	Product Height	100 mm
	Product Width	150 mm
	Product Weight	.25 kg
	Compliances	CE marking
	Certifications	
Product specifications	Talk back	Yes
	Number of transistor outputs	4
	Operating temperature - min	-10 °C
	With housing	
	Digital transmission	
	EN 50131 Grade	Not applicable
	Type of communicator	Speech dialler
	VdS Class	None
	Current normal	50 mA
	With power adaptor	No
	Internal aerial	
	Listen in	
	Voice Transmission (AWAG)	
	Radio frequency	850/900/1800/1900MHz
	Messages - SMS	8
	Operating temperature - max	55 °C
	Programming display	LCD
	X.31/X.25	
	Analogue connection	
	Temperature Sensor	
	Messages - speech	
	Wired input type	CC
	Supply - max	28 V
	Remote access	
	Enclosure Colour	White
	ISDN connection	
	Mounting	Surface
	Number of relay outputs	
	ATS rating	
	Type of current	DC
	Maximum number of inputs	
	Arc format	
	Current - max	170 mA
	Enclosure material	Plastic

	Contacts	10
	Supply - min	12 V
	Radio exchange method (GSM)	
	Environmental class	Class II
	Technology type	GSM