SIGMA XT ANCILLARIES

Extinguishant Hold Off

Features

- > Shrouded push button to prevent inadvertent operation
- Activation resistor included
- Compatible with all Sigma XT and Sigma XT+ models
- Robust steel surface mount enclosure
- Flush mount collar available*



Description

The K91000M10 Hold Off Unit provides a robust and convenient point to apply a temporary hold to release of fire protection extinguishant release.

The robust pushbutton is shrouded to prevent accidental operation and is coloured to comply with the requirements of BS7273-1.

The robust enclosure allows for either surface mounting or flush with optional collar. Part M10FCLGT*.

Specification

Construction	1.2mm mild sheet steel
IP rating	IP30
Colour - lid & box	BS 00 A 05 grey - fine texture
Weight	ıkg
Contacts	1x Normally Open, 1x Normally Closed
Operating Temperature	-5°C to +40°C
Knockouts	20mm
Trigger Resistor	470R 1 Watt

Equipment		
Product Code	Description	Size
K91000M10	Extinguishant Hold Off Switch Unit - Green Button	102 X 102 X 50
KB91000M10	Extinguishant Hold Off Switch Unit - Red Button	102 X 102 X 50
M10FCLGT	Flush Mount Collar	N/A



Datasheet DS86b/04/17

For further information visit www.kentec.co.uk Kentec Electronics Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Kentec Electronics Ltd. to be a complete and up-to-date description.