Wired keypad series with options to suit application



As well as having a modern, small and discreet design the KEY-K01, KEY-KP01 and KEY-KPZ01 have a choice of non-prox (K), prox (KP) or prox with zones (KPZ).

The prox keypads have connections for an external prox reader to be connected in addition to the internal prox. To add greater flexibility to the KEY-KPZ01 you can select the option of having two zones on board for an even faster connection of zones.

At a glance...

- A navigation key for easy access to the user and installer menus
- A status LED that can be turned on or off from within the keypad menu
- An internal prox reader (not available on the KEY-K01)
- Built in panic button enabled in programming
- One programmable transistorised output (KEY-KPZ01 Only)
- External prox reader connections for KEY-EP (Not available on KEY-K01)



Scantronic product data sheet

Product specification

Product Code	KEY-K01	KEY-KP01	KEY-KPZ01
Zone Inputs	0	0	2
Outputs	0	0	1
Loudspeaker connection	No	No	Yes
EN 50131 grade	PD6662:2017 BS8243:2010 + A1 2014, EN50131 Grade 2 or Grade 3		
Environmental class	Environmental class 2		
Operating temperature (°C)	-10°C to 55°C @ 75% RH		
Display with LED indication	Yes		
Zones	0	0	2 zones available
Dimensions	128 x 128 x 29mm		



128 mm

128 mm

Compare product compatibility with our easy to read chart: www.eaton.com/security-works-with

