
SC517/(WH or BR)/G2

Surface Contact

With Microswitch Tamper

Max operating gap 20mm.



In case of uneven surface, use the spare screw to operate the tamper. The drawing above maybe used as a template to mark the position.

CQR Security. 125, Pasture Road, Moreton, Wirral. CH46 4TH, United Kingdom

Tel: +44 (0) 151 606 9595 Support: +44 (0) 151 606 6311 email: info@cqr.co.uk Web http://www.cqr.co.uk


Complies with EN50131. Security Grade 2 Environmental class II

SC517/(WH or BR)/G2

Surface Contact

With Microswitch Tamper

Max operating gap 20mm. Microswitch Spare



In case of uneven surface, use the spare screw to operate the tamper. The drawing above maybe used as a template to mark the position.

CQR Security, 125, Pasture Road, Moreton, Wirral. CH46 4TH, United Kingdom

Tel: +44 (0) 151 606 9595 Support: +44 (0) 151 606 6311 email: info@cqr.co.uk Web http://www.cqr.co.uk

Complies with EN50131. Security Grade 2 Environmental class II

SC517/(WH or BR)/G2

Surface Contact

With Microswitch Tamper

Max operating gap 20mm.
Microswitch Spare

Tamper'
Alarm
In case of uneven surface, use the spare screw to operate the tamper.
The drawing above maybe used as a template to mark the position.

CH46 4TH, United Kingdom
Tel: +44 (0) 151 606 9595 Support: +44 (0) 151 606 6311
email: info@cqr.co.uk Web http://www.cqr.co.uk

CQR Security. 125, Pasture Road, Moreton, Wirral.

Complies with EN50131. Security Grade 2 Environmental class II

SC517/(WH or BR)/G2

Surface Contact

With Microswitch Tamper

Max operating gap 20mm.
Microswitch Spare

Tamper
Alarm

In case of uneven surface, use the spare screw to operate the tamper. The drawing above maybe used as a template to mark the position.

CQR Security. 125, Pasture Road, Moreton, Wirral. CH46 4TH, United Kingdom

Tel: +44 (0) 151 606 9595 Support: +44 (0) 151 606 6311 email: info@cqr.co.uk Web http://www.cqr.co.uk

Complies with EN50131. Security Grade 2 Environmental class II

SC517/(WH or BR)/G2

Surface Contact

With Microswitch Tamper

Max operating gap 20mm.
Microswitch Spare

Tamper

Alarm In case of uneven surface, use the spare screw to operate the tamper. The drawing above maybe used as a template to mark the position.

CQR Security. 125, Pasture Road, Moreton, Wirral. CH46 4TH, United Kingdom

Tel: +44 (0) 151 606 9595 Support: +44 (0) 151 606 6311 email: info@cgr.co.uk Web http://www.cgr.co.uk


Complies with EN50131. Security Grade 2 Environmental class II

SC517/(WH or BR)/G2

Surface Contact

With Microswitch Tamper

Max operating gap 20mm. Microswitch Spare



In case of uneven surface, use the spare screw to operate the tamper. The drawing above maybe used as a template to mark the position.

CQR Security. 125, Pasture Road, Moreton, Wirral. CH46 4TH, United Kingdom

Tel: +44 (0) 151 606 9595 Support: +44 (0) 151 606 6311 email: info@cgr.co.uk Web http://www.cgr.co.uk

Complies with EN50131. Security Grade 2 Environmental class II

SC517/(WH or BR)/G2

Surface Contact

With Microswitch Tamper

Max operating gap 20mm.
Microswitch Spare

Tamper

Alarm / In case of uneven surface, use the spare screw to operate the tamper. The drawing above maybe used as a template to mark the position.

CQR Security. 125, Pasture Road, Moreton, Wirral. CH46 4TH, United Kingdom

Tel: +44 (0) 151 606 9595 Support: +44 (0) 151 606 6311 email: info@cqr.co.uk Web http://www.cqr.co.uk

Complies with EN50131. Security Grade 2 Environmental class II

SC517/(WH or BR)/G2

Surface Contact

With Microswitch Tamper

Max operating gap 20mm.
Microswitch Spare

`Tamper' Alarm ′

In case of uneven surface, use the spare screw to operate the tamper. The drawing above maybe used as a template to mark the position.

CQR Security. 125, Pasture Road, Moreton, Wirral. CH46 4TH, United Kingdom

Tel:+44 (0) 151 606 9595 Support: +44 (0) 151 606 6311 email:info@cgr.co.uk Web http://www.cgr.co.uk

Complies with EN50131. Security Grade 2 Environmental class II