



3 I/O PLUS

ADDRESSABLE TRIPLE INPUT/OUTPUT MODULE



The 3 I/O PLUS Modules are fully monitored loop powered devices which permit the interfacing of third party equipment with the Fire Alarm Control panel using normally open dry contact connections. Each module can be fitted with a maximum of 3 inputs and 3 outputs. The connection to each input is monitored for fault (open or short circuit) and Alarm conditions.

The interface is used to monitor the contacts of an external system which must be interfaced to the Fire Alarm System, for example a Flow Switch in a sprinkler system to indicate if the sprinklers have been activated or extinguishant level monitoring in Gas Extinguishing Systems, etc.

Module is provided with a loop short-circuit isolator and with up to 3 voltage free single pole change over relay outputs. The output relays are always powered directly from the detection loop. It is not required to use an external 24V DC power supply. Relay operation is confirmed by an onboard Red LED. A 8 way D.I.L. switch is provided to configure the module's address. This value can be set in the range 1 to 125. The following programmable functions are available: Input Activation Mode, Delayed Input Alarm Activation, Output Delayed Activation.

KEY FEATURES

- Fast Activation Response
- Loop Powered
- Status LEDs for each I/O and O/P
- Low Power Consumption
- Module features an integral short-circuit loop isolator

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------------|---|
| SUPPLY VOLTAGE | Loop Powered 20V to 30V DC |
| LOOP CURRENT - QUIESCENT | 1.4 mA (1 ch.) - 1.5 mA (2 ch.) - 1.6 mA (3 ch.) |
| LOOP CURRENT - ALARM / SHORT-CIRCUIT | IQ+ 1.2 mA for each I/P in alarm / IQ+ 1.4 mA max. |
| LOOP CURRENT - OPEN CIRCUIT | IQ+ 1.0 mA max. |
| LOOP CURRENT - OUTPUT ACTIVE | IQ+ 1.1 mA for each O/P activated |
| OUTPUT RELAY CONTACT RATING | 2A 30V DC / 0.5A 125V AC |
| CABLE SIZE | 0.5-2.5 mm ² |
| COLOUR / CASE MATERIAL | White & Transparent / ABS |
| OPER. TEMPERATURE / MAX. HUMIDITY | -10°C to 50°C / 95% RH Non-Condensing |
| DIMENSIONS / WEIGHT | 150 (W) x 90 (L) x 32 (H) mm / 216 g inc. packaging |

For EN54-13 compliance, please check the control panel manual specifications.



© 211102

Global Fire Equipment SA

Sítio dos Barrabés, Armazém Nave Y, Caixa Postal 908-Z
8150-016 São Brás de Alportel PORTUGAL

Telephone: (00351) 289 896 560 / Email: info@globalfire-equipment.com / Web: www.globalfire-equipment.com



GSS GROUP

ORDER CODE

| | | |
|-------------------------------|---|---------------|
| 3 I/O PLUS - 1 CHANNEL | ADDRESSABLE SINGLE INPUT/OUTPUT MODULE - W/ ISOLATOR - W/ DUAL GANG BOX | 1328-CPR-0542 |
| 3 I/O PLUS - 2 CHANNEL | ADDRESSABLE DOUBLE I/O MODULE - W/ ISOLATOR - W/ DUAL GANG BOX | 1328-CPR-0543 |
| 3 I/O PLUS - 3 CHANNEL | ADDRESSABLE TRIPLE I/O MODULE - W/ ISOLATOR - W/ DUAL GANG BOX | 1328-CPR-0544 |



© 211102

Global Fire Equipment SA

Sítio dos Barrabés, Armazém Nave Y, Caixa Postal 908-Z
8150-016 São Brás de Alportel PORTUGAL

Telephone: (00351) 289 896 560 / **Email:** info@globalfire-equipment.com / **Web:** www.globalfire-equipment.com



GSS GROUP