



VALKYRIE AS IP65

**ADDRESSABLE WALL MOUNT
SOUNDER/ BEACON
OUTDOOR USE-IP65**



1328-CPR-0299
CERTIFIED

The VALKYRIE AS IP65 is a Wall Mounted Addressable Sounder/ Beacon with low power consumption. It is specifically designed to be used outdoors. Up to 32 individually addressed sounders can be installed per loop occupying address 94 to 125. The address is set using switches 1 to 5 of the 8 way DIL switch. Four different tones are available and selected using DIL switches 6 and 7.

When individual address reporting is not required, VALKYRIE AS IP65 can be configured as a Shadow Sounder. In this case sounders do not occupy an address in the loop thus freeing up addresses for more detection devices. Shadow sounders do not report back to the control panel so their presence on the loop is not monitored. Shadow sounders draw current from the loop (10 mA in alarm) and must be included in loop load calculations.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	Loop Powered - 20 V to 30 V DC
LOOP CURRENT - QUIESCENT	550 uA max. with isolator
LOOP CURRENT - SOUNDER/BEACON ACTIVE	10 mA - 280 mW @ 28 V DC inc. isolator
MAXIMUM SOUNDER OUTPUT	100 dB (@ 1 meter - 30 V DC)
RESET/START-UP TIMES	20 seconds max.
PROTECTION CATEGORY	Type B - Outdoor Use / Rating IP65
CABLE SIZE	0.5-2.5 mm ²
COLOUR	Red
CASE MATERIAL	ABS and PC
OPER. TEMPERATURE	-25°C to 70°C
MAX. HUMIDITY	95% RH Non-Condensing
DIMENSIONS	112 (D) x 110 (H) mm inc. base
WEIGHT	315 g inc. base & 350 g inc. packaging

For EN54-13 compliance, please check the control panel manual specifications.

ORDER CODE

VALKYRIE AS IP65	ADDRESSABLE WALL SOUNDER WITH ISOLATOR - IP65 RATED	1328-CPR-0299
VALKYRIE ASBI IP65	ADDRESSABLE WALL SOUNDER/ BEACON WITH ISOLATOR - IP65 RATED	1328-CPR-0299

