



# VALKYRIE CS

## CONVENTIONAL WALL MOUNT SOUNDER/ BEACON



The VALKYRIE CS is a wall mounted Conventional Sounder/ Beacon with low power consumption. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

### TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	20 V to 30 V DC
CURRENT - SOUNDER/BEACON ACTIVE	10 mA - 280 mW @ 28 V DC
MAXIMUM SOUNDER OUTPUT	97.5 dB (@ 1 meter - 30 V DC)
CABLE SIZE	0.5-2.5 mm <sup>2</sup>
RESET/START-UP TIMES	20 seconds max.
PROTECTION CATEGORY	Type A - Indoor Use / Rating IP21C
COLOUR	White or Red
CASE MATERIAL	ABS and PC - Flame Retardant rating IL 94 V2
OPER. TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
DIMENSIONS	110 (D) x 85 (H) mm inc. base
WEIGHT	254 g inc. base & 304 g inc. packaging

*For EN54-13 compliance, please check the control panel manual specifications.*

### ORDER CODE

<b>VALKYRIE CS-WHITE</b>	CONVENTIONAL WALL SOUNDER - WHITE	1328-CPR-0287
<b>VALKYRIE CS-RED</b>	CONVENTIONAL WALL SOUNDER - RED	1328-CPR-0287
<b>VALKYRIE CSB-WHITE</b>	CONVENTIONAL WALL SOUNDER/ BEACON - WHITE	1328-CPR-0287
<b>VALKYRIE CSB-RED</b>	CONVENTIONAL WALL SOUNDER/ BEACON - RED	1328-CPR-0287