



Article number:A-3212DZ-EB 10E  
Alternative products: A-3224DZ, A-3248DZ

## Specifications

Power source	100 - 240 V AC, 50 / 60 Hz
Rated output	120 W
Power source	100 - 240 V AC, 50 / 60 Hz
Rated output	120 W
Frequency response	50 Hz - 20 kHz
Control input	Priority Control Input, removable terminal block
Frequency response	50 Hz - 20 kHz
Power consumption	44 W(AC operation at 1/8 maximum output without clip)
S/N ratio	60 dB
Number of channels	5
Connectable microphones	4
S/N ratio	60 dB
Inputs	MIC 1 : 1 mV (-60dB*), 600 Ω, balanced, phone jack, selectable to RJ45 MIC 2-3 : 1 mV (-60dB*), 600 Ω, balanced, phone jack MIC 4 : 1 mV (-60dB*), 600 Ω, balanced, phone jack, selectable to AUX 1 AUX 1 : 100 mV(-20dB*), 10 kΩ, unbalanced, RCA pin jack, selectable to MIC 4 AUX 2 : 100 mV(-20dBc), 10 kΩ, unbalanced, RCA pin jack PRIORITY : 0 dB*, 600 Ω, unbalanced removable terminal block
Control input	Priority Control Input, removable terminal block
Outputs	Speaker Output : in screw type terminal Direct Line (selectable) : 83 Ω (100V) or 4 Ω Zone Selection : 5 zones simultaneously selectable Rec Out : 0 dB*, 600 Ω, unbalanced, RCA pin jack
Finish	ABS resin, Steel plate, black,
Operating temperature	0°C to +40°C (32°F to 104°F)



# A-3212DZ

---

Appearance