

PJ-154BS

PROJECTION SPEAKER

The PJ-154BS is the voice alarm certification product. 2 way speaker system is suitable for announcement and music use in wide frequency range. Stylish and outstanding design inspired by the finest lighting fixtures. A supplied swivel bracket accessory allows for flexible speaker angle adjustment.



Article number: PJ-154BS
 Alternative products: PE-154BS, PE-154EN,
 PJ-202DL

Specifications

Sensitivity (1#V, 1#m)	91 dB 500 Hz - 5 kHz, pink noise) 87 dB (1 W, 1 m at 100 Hz to 10 kHz pink noise) 75 dB (1 W, 4 m at 100 Hz to 10 kHz pink noise)
Frequency response	70 Hz - 20 kHz
Max. SPL (1 m)	99 dB 15 W, 1 m at 100 Hz to 10 kHz, pink noise 87 dB (15 W, 4 m at 100 Hz to 10 kHz, pink noise)
Connection	Ceramic screw terminals, thermal fuse in external connection box
Directivity Angle catalogue output	500 Hz: 360°/360° 1 kHz: 170°/170° 2 kHz: 90°/90° 4 kHz: 70°/70°
Rated input (high impedance)	15 W (100 V), 7,5 W (70 V)
Tappings	100 V : 670 Ω (15 W) / 1 kΩ (10 W) / 2 kΩ (5 W) 70 V : 670 Ω (7.5 W) / 1 kΩ (5 W) / 2 kΩ (2.5 W)
Speaker component	Low: 5" cone-type, High: 1" balanced dome tweeter
Finish	HIPS resin, off-white (RAL 9010 or equivalent), Grille: Surface-treated steel plate net, off-white (RAL 9010 or equivalent color), paint
Operating temperature	-10 °C to +50 °C (14 °F to 122 °F)

PJ-154BS

PROJECTION SPEAKER

Appearance

