

# SC-615BS

## PAGING HORN SPEAKER

The SC-615BS is the voice alarm certification product. This speaker can be a clearer announcement for voice alarm. The SC-615BS Paging horn speaker features an aluminium horn flare and stainless steel bracket for all weather durability. The SC-615BS unique oval shape horn enhances excellent speech clarity.



Article number: SC-615BS  
 Alternative products: SC-630M EB-Q,  
 SC-615M

### Specifications

Sensitivity (1#V, 1#n)	109 dB 500 Hz - 2,5 kHz, peak level
Frequency response	315 Hz - 12.5 kHz
Max. SPL (1 m)	110 dB 15 W, 100 Hz - 10 kHz, pink noise
Connection	Screw terminal (steatite), can be bridge-connected
Directivity Angle catalogue output	500 Hz: 360°/360° 1 kHz: 160°/200° 2 kHz: 85°/115° 4 kHz: 45°/60°
Rated input (high impedance)	15 W
Tappings	100 V: 670 Ω (15 W) / 1 kΩ (10 W) / 2 kΩ (5 W) / 3.3 kΩ (3 W) 70 V: 330 Ω (15 W) / 670 Ω (10 W) / 1 kΩ (5 W) / 2 kΩ (2.5 W) / 3.3 kΩ (1.5 W)
Finish	Aluminium, powder coating, off-white (RAL 9010 or equivalent), Reflector horn, trans case and terminal cover: ABS resin, off-white (RAL 9010 or equivalent) Bracket, screws and bolts: Stainless steel
Operating temperature	-20 °C to +55 °C (-4 °F to 131 °F)

# SC-615BS

PAGING HORN SPEAKER

Appearance

