

Datasheet

RECEIVERS/ RX26-XPL1V - 1 Relay Receiver

Product description

The RX26-XPL1 series allows the easy operation and programming of the RX26-XPL whilst increasing the memory to 500 transmitters and adding an IP55 enclosure.

Each relay can be separately configured for pulse, timed or latch modes, with a maximum contact rating of 24VA at 60V. Security is upheld by the use of Keeloq rolling code decryption.

The RX26-XPL1 also comes in 12-24ac/dc version (RX26-XPL1V). An input is available for the SEA433 tuned aerial.



Key features


- 1 relay
- Up to 500 transmitter memory capacity
- White housing, black lid
- Keeloq® Hopping Code

 Certification

 DEEE

 Certification

 IP55

 -20°C to 70°C

All the information contained within this document (pictures, drawing, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. - March 2020 - CDVI_RX26-XPL1V_DS_01_EN_A4_C

Product Information

Receiver type: Superheterodyne
Material: Polycarbonate housing
Frequency: 433.92MHz
Modulation: AM/ASK
Encoding: Keeloq® Hopping code
Number of code combinations: 2exp64
Memory capacity: 500 transmitters

Relays

Number of relays: 1
Contact: NO/NC
Operating mode: Pulse, step, timed, on-off
Delay: 1sec. to 23h59min

Electrical specifications

Power supply: 230 Vac - 50 Hz
Max power on relay output: 16 A
Consumption: 10 mA @230 Vac

