

# Datasheet

## RECEIVERS/ RX26-XPL1P - 1 Relay Receiver

### Product description

The RX26-XPL1 series allows the easy operation and programming of the RX26-XPL whilst increasing the memory to 500 transmitters and adding an IP55 enclosure.

Each relay can be separately configured for pulse, timed or latch modes, with a maximum contact rating of 24VA at 60V. Security is upheld by the use of Keeloq rolling code decryption.

The RX26-XPL1 also comes in 230Vac version (RX26-XPL1V). An input is available for the SEA433 tuned aerial.



### Key features

- 1 relay
- Up to 500 transmitter memory capacity
- White housing, black lid
- Keeloq® Hopping Code



*Certification*



*DEEE*



*Certification*



*IP55*



*-20°C to 70°C*

All the information contained within this document (pictures, drawing, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. - March 2020 - CDVI\_RX26-XPL1P\_DS\_01\_EN\_A4\_C

## Product Information

**Receiver type:** Superheterodyne  
**Material:** Polycarbonate housing  
**Frequency:** 433.92MHz  
**Modulation:** AM/ASK  
**Encoding:** Keeloq® Hopping code  
**Number of code combinations:** 2exp64  
**Memory capacity:** 500 transmitters

## Relays

**Number or relays:** 1  
**Contact:** NO/NC  
**Operating mode:** Pulse, step, timed, on-off  
**Delay:** 1sec. to 23h59min

## Electrical specifications

**Power supply:** 12 to 24 Vac/dc  
**Max power on relay output:** 16A/ 230Vac  
**Consumption:**  
@ 12Vdc = 90mA - @ 24Vac = 86mA  
@ 24Vdc = 58mA - @ 24Vac = 190mA

