

Datasheet

ELECTROMAGNETIC LOCKS/ S300DS - Internal Surface Maglock with Door Position Monitor

Product description

The maglock is a surface maglock with a holding force of up to 300kg, offering high quality and high performance locking. Part of the features include a blue LED to signal the lock status and security "catch" ropes to prevent the magnetic lock from falling, ensuring a mounting without risk of injury.

The door positioning monitor creates a more secure system as it allows for monitoring the door position open or closed. It is ideal for auto-relock control and saves fitting door contacts.

**PATENTED
BREVETÉ**



Key features

- Surface mount maglock
- Auto-relock control
- Up to 300kg holding force
- Z&L bracket available
- Visual indication with LED



CE Certification

 DEEE

RoHS Certification

IP IP42

All the information contained within this document (pictures, drawing, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. - April 2021 - CDVI_S300DS_DS_01_EN_A4_C

Product Specifications

Maglock

Holding force: up to 300kg

Door position monitor

Changeover contact: fitted to magnet cover plate

Armature extension: houses the contact magnet

Output: NO, NC

Electrical Specifications

Maglock

Voltage: 12/24Vdc

Current: @12Vdc = 550mA,
@24Vdc = 275mA

Door position monitor

Contact rating: 100mA

