

Datasheet

RECEIVERS/ RX26-XPL5 - 2 Relay Receiver

Product description



The RX26-XPL5 series allows the easy operation and programming of the RX26-XPL whilst increasing the memory to 500 transmitters and adding an IP55 enclosure.

Each of the 2 relays can be separately configured for pulse, timed or latch modes, with a maximum contact rating of 24VA at 60V. Security is upheld by the use of Keeloq rolling code decryption.

The RX26-XPL5 also comes in a 4 relay version ([RX26-XPL54](#)). An input is available for the SEA433 tuned aerial.



Key features


- 2 relays
- Up to 500 transmitter memory capacity
- White housing, black lid
- Keeloq® Hopping Code

 *Certification*

 *DEEE*

 *Certification*

 *IP55*

 *-20°C to 70°C*

All the information contained within this document (pictures, drawing, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. - March 2020 - CDVI_RX26-XPL5_DS_01_EN_A4_C

Product Information

Receiver type: Superheterodyne
Material: Polycarbonate housing
Frequency: 433.92MHz
Modulation: AM/ASK
Encoding: Keeloq® Hopping code
Number of code combinations: $2^{\text{exp}64}$
Memory capacity: 500 transmitters

Relays

Number or relays: 2
Contact: 1 NO, 1 NO/NC
Operating mode: Pulse, step, timed
Delay: 1sec. to 23h59min

Electrical specifications

Power supply: 12 or 24 Vac/dc
Max power on relay output: 24VA max 60V
Consumption: 25 mA to 90 mA (max)

